

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2015 Version number 12 Revision: 20.02.2015

1 Identification of the substance/mixture and of the company/undertaking

- . 1.1 Product identifier
- . Trade name: UHU PU MAX POLIURETANO LIQUIDO BOT 250G*12 ES
- . CAS Number:

9016-87-9

. EC number:

202-966-0

. Index number:

615-005-01-6

- . 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- . Application of the substance / the mixture Adhesive
- . 1.3 Details of the supplier of the safety data sheet
- . Manufacturer/Supplier:

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes

tel. +31 88 3235700 fax. +31 88 3235800

e mail: msds@bison.boltongroup.nl

- . Further information obtainable from: Bison QESH
- . 1.4 Emergency telephone number: +31 88 3235700

2 Hazards identification

- . 2.1 Classification of the substance or mixture
- . Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20-40-48/20: Harmful by inhalation. Limited evidence of a carcinogenic

effect. Harmful: danger of serious damage to health by prolonged

exposure through inhalation.

Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

Information concerning particular hazards for human and environment:

. 2.2 Label elements

Not applicable.

. Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 2)

www.uhu.com



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2015 Version number 12 Revision: 20.02.2015

Trade name: UHU PU MAX POLIURETANO LIQUIDO BOT 250G*12 ES

(Contd. of page 1)

. Code letter and hazard designation of product:



Xn Harmful

. Risk phrases:

20 Harmful by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

40 Limited evidence of a carcinogenic effect.

42/43 May cause sensitisation by inhalation and skin contact.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

. Safety phrases:

23 Do not breathe vapour.

24/25 Avoid contact with skin and eyes.

- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 37 Wear suitable gloves.
- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 51 Use only in well-ventilated areas.

. Special labelling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer

- . 2.3 Other hazards
- . Results of PBT and vPvB assessment
- . **PBT:** Not applicable.
- . vPvB: Not applicable.

3 Composition/information on ingredients

- . 3.1 Substances
- . CAS No. Description

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

- . Identification number(s)
- . EC number: 202-966-0
- . Index number: 615-005-01-6
- . Dangerous components: Void

4 First aid measures

- . 4.1 Description of first aid measures
- . General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

. After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stable in side position for transportation.

- . After skin contact: Immediately wash with water and soap and rinse thoroughly.
- . After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

GB

www.uhu.com 2/7



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2015 Version number 12 Revision: 20.02.2015

Trade name: UHU PU MAX POLIURETANO LIQUIDO BOT 250G*12 ES

(Contd. of page 2)

- . After swallowing: Do not induce vomiting; call for medical help immediately.
- . 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- . 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- . 5.1 Extinguishing media
- . Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

. 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- . 5.3 Advice for firefighters
- . Protective equipment: Mount respiratory protective device.

6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- . 6.2 Environmental precautions: No special measures required.
- . 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.
. 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

. 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

- . Information about fire and explosion protection: No special measures required.
- . 7.2 Conditions for safe storage, including any incompatibilities
- . Storage:
- . Requirements to be met by storerooms and receptacles: No special requirements.
- . Information about storage in one common storage facility: Not required.
- . Further information about storage conditions: Keep receptacle tightly sealed.
- . 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- . Additional information about design of technical facilities: No further data; see item 7.
- . 8.1 Control parameters
- . Ingredients with limit values that require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL () Short-term value: 0.07 mg/m³
 Long-term value: 0.02 mg/m³
 Sen; as -NCO

. Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

GB

www.uhu.com 3/7



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2015 Version number 12 Revision: 20.02.2015

Trade name: UHU PU MAX POLIURETANO LIQUIDO BOT 250G*12 ES

(Contd. of page 3)

- . 8.2 Exposure controls
- . Personal protective equipment:
- . General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

. Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

. Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

. Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

. For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

PVC or PE gloves

. Eye protection:



Tightly sealed goggles

. Body protection: Use protective suit.

9 Physical and chemical properties

- . 9.1 Information on basic physical and chemical properties
- . General Information

. Appearance:

Form: Liquid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.pH-value: Not determined.

. Change in condition

Melting point/Melting range: < 0 °C Boiling point/Boiling range: 190 °C

(Contd. on page 5)

GB -

www.uhu.com 4/7



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2015 Version number 12 Revision: 20.02.2015

Trade name: UHU PU MAX POLIURETANO LIQUIDO BOT 250G*12 ES

(Contd. of page 4)

. Flash point: > 110 °C

. Flammability (solid, gaseous): Not applicable.

. Ignition temperature: 400 °C

Decomposition temperature: Not determined.Self-igniting: Not determined.

. Danger of explosion: Product does not present an explosion hazard.

. Explosion limits:

Lower: Not determined.
Upper: Not determined.

. Vapour pressure at 25 °C: 0.0002 hPa

Density at 20 °C:
Relative density
Not determined.
Vapour density
Not determined.
Evaporation rate
Not determined.

. Solubility in / Miscibility with

water: Not miscible or difficult to mix.

. Partition coefficient (n-octanol/

water):
Not determined.

. Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

Solids content: 100.0 %

. 9.2 Other information No further relevant information available.

10 Stability and reactivity

. 10.1 Reactivity

. 10.2 Chemical stability

. Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

. 10.3 Possibility of hazardous reactions

Reacts with alcohols.

Reacts with water.

Reacts with alkali, amines and strong acids.

- . 10.4 Conditions to avoid No further relevant information available.
- . 10.5 Incompatible materials: No further relevant information available.
- . 10.6 Hazardous decomposition products:

Danger of forming toxic pyrolysis products.

11 Toxicological information

- . 11.1 Information on toxicological effects
- . Acute toxicity:
- . Primary irritant effect:
- . on the skin: Irritant to skin and mucous membranes.
- . on the eye: Irritating effect.
- . Sensitisation:

Sensitisation possible through inhalation.

(Contd. on page 6)

www.uhu.com 5/7

GB -



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2015 Version number 12 Revision: 20.02.2015

Trade name: UHU PU MAX POLIURETANO LIQUIDO BOT 250G*12 ES

(Contd. of page 5)

Sensitisation possible through skin contact.

12 Ecological information

- . 12.1 Toxicity
- . Aquatic toxicity: No further relevant information available.
- . 12.2 Persistence and degradability No further relevant information available.
- . 12.3 Bioaccumulative potential No further relevant information available.
- . 12.4 Mobility in soil No further relevant information available.
- . Additional ecological information:
- . General notes: Generally not hazardous for water
- . 12.5 Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . vPvB: Not applicable.
- . 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- . 13.1 Waste treatment methods
- . Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- . Uncleaned packaging:
- . Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14 Transport information

. 14.1 UN-Number

. ADR, ADN, ADN, IMDG, IATA Void

. 14.2 UN proper shipping name

. ADR, ADN, ADN, IMDG, IATA Void

. 14.3 Transport hazard class(es)

. ADR, ADN, ADN, IMDG, IATA

. Class Void

. 14.4 Packing group

. ADR, ADN, IMDG, IATA Void

. 14.5 Environmental hazards:

. Marine pollutant: No

. 14.6 Special precautions for user Not applicable.

. 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC

Code Not applicable.

. Transport/Additional information:

. IMDG

. Remarks: Under certain conditions substances in Class

3 (flammable liquids) can be classified in

packinggroup III.

See IMDG, Part 2, Chapter 2.3, Paragraph

2.3.2.2

(Contd. on page 7)

GB

www.uhu.com 6/7



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2015 Version number 12 Revision: 20.02.2015

Trade name: UHU PU MAX POLIURETANO LIQUIDO BOT 250G*12 ES

(Contd. of page 6)

15 Regulatory information

- . 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- . Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

. Code letter and hazard designation of product:



Xn Harmful

. Risk phrases:

20 Harmful by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

40 Limited evidence of a carcinogenic effect.

42/43 May cause sensitisation by inhalation and skin contact.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

. Safety phrases:

- 23 Do not breathe vapour.
- 24/25 Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 37 Wear suitable gloves.
- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 51 Use only in well-ventilated areas.

. Special labelling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- . Department issuing MSDS: QESH Department
- . Contact: Reach coördinator
- . * Data compared to the previous version altered.

www.uhu.com 7/7