

## FRONTAL DE INSPECCIÓN RECARGABLE USB

### Características de Producto

- Ligero y resistente
- Encendido/Apagado mediante Interruptor
  - Sensor PIR para la operación "Manos Libres"
- Orientable hasta 60° para múltiples aplicaciones
- 5 modos de funcionamiento - 100%, 50%, Intermitente, Luz Roja, Rojo Intermitente




CAT NO.	LÚMENES LUMINARIA	POTENCIA	EFICACIA Llm/cW	PESO (kg)	CRI	IK	RANGO TEMP (°C)	L/B VIDA ÚTIL
LILH15P65	150	30W	50	1,44	>80	IK07	TBC	TBC

### Dimensiones

STANDARD	DESCRIPTION
EN 60598-1	Luminaires Part 1 General requirements and tests
EN 60598-2-4	Luminaires: Particular requirements - Portable General Purpose Luminaires
EN 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements
EN 62133	Secondary Cells and Batteries Containing Alkaline or Other Non-Acid. Electrolytes - Safety Requirements
EN 55015	Limit and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
EN 61547	Equipment for general lighting purposes. EMC immunity requirements
EN 61000-3-2	Electromagnetic compatibility (EMC)
EN 61000-3-3	Electromagnetic compatibility (EMC)
EN 62471	Photobiological safety of lamps and lamp systems

**LUCECO**

 Esta luminaria lleva lámparas LED incorporadas.

A+  
A\*  
A  
B  
C  
D  
E

} LED

Las lámparas de esta luminaria no son recambiables.

874/2012 